

## SAFETY FOOTWEAR

05.11.2020 SBU-F-PGM-PM

Product Datasheet uvex 1 G2 68381 - 68384 S3 SRC



## UVEX ARBEITSSCHUTZ GmbH, Würzburger Str. 181-189, D-90766 Fürth

General features	<ul> <li>ultra-lightweight S3 safety shoe</li> </ul>
	<ul> <li>made from synthetic materials, making it suitable for</li> </ul>
	people allergic to chrome
	<ul> <li>all sole materials are free of silicone, plasticisers and</li> </ul>
	other paint wetting impairment substances
	<ul> <li>individually adjustable elastic laces for quick release,</li> </ul>
	normal laces also provided
Protection features	new, innovative uvex i-PUREnrj sole technology with
	the highest level of shock-absorbing properties at the
	forefoot and at the heel, excellent rebound over the
	entire midsole and optimal stability thanks to the foam
	heel basket
	<ul> <li>meets the ESD specification with volume resistance</li> </ul>
	under 35 megaohms
	<ul> <li>new wider 100% metal-free uvex xenova® safety toe</li> </ul>
	cap for more toe room and optimum fit - compact
	design, anatomical shape, good lateral stability and no
	thermal conductivity
	<ul> <li>penetration-resistant, non-metallic midsole in</li> </ul>
	accordance with current safety standards, does not
	restrict flexibility of the shoe
	<ul> <li>TPU scuffcap to protect against abrasion</li> </ul>
Comfort features	<ul> <li>outstanding wearer comfort thanks to a newly</li> </ul>
	developed last and climate-optimised, breathable
	materials
	<ul> <li>virtually seam-free, hydrophobic upper in high-tech</li> </ul>
	microvelour to eliminate pressure points
	removable antistatic comfortable insole with a

Rev. St. 1 Datum: 02.06.2016 Seite 1 von 2

	moisture transport system, additional shock absorption around the heel and forefoot and excellent support for the arch soft padding on the dust tongue and collar sizes 35 to 40 have been produced using a women's last
Outsole	<ul> <li>ergonomically designed uvex x-tended grip outsole incorporates the latest biomechanical research, is particularly durable and therefore offers excellent slip resistance. The tread is particularly suited to industrial floors and rough surfaces</li> <li>excellent cushioning and extremely flexible</li> <li>excellent slip resistance, self-cleaning tread</li> <li>resistant to oil and petrol</li> <li>resistant to temperatures for short periods up to +120°C</li> </ul>
Certificates	Certified with uvex medicare for individual, orthopedic inlay soles and individual adjustments of the sole unit such as overall increase, inside and outside increase and other solutions.
Areas of application	light applications
Technical data	uvex 1 G2 safety shoe S3 SRC  Artno. 68381 68382 68383 68384  Width 10 11 12 14  Standard EN ISO 20345:2011 S3 SRC  Size 35-52
Accessories	Removable uvex 1 G2 comfortable climatic insole (article no.: 94907 - 94900)  • improved full-surface shock absorption • ultra-breathable, moisture-absorbing and quick-drying materials • shock absorption zones support natural movement of the foot • non-irritating, comfortable surface structure • anti-static properties • arch support  Laces • black (Artno.: 9599.9 09) • elastic laces (Artno.: 9591.200)

Rev. St. 1 Datum: 02.06.2016 Seite 2 von 2